

84N Series

Sheet Metal Press Room Gripper Products

DESTACO Introduces the newest addition to its line of stamping press sheet metal gripping solutions.

The Accelerate[®] sheet metal press room gripper is half the weight and more compact, with faster actuation — when compared to our closest competition⁽¹⁾ — without sacrificing grip force which measures up to 1000 N at 5 bar.

The lighter, smaller and faster 84N series gripper accelerates stamping press operations by helping customers produce more stamped parts per hour with higher efficiency while reducing moment forces and overall system wear and tear.



Product Highlights/Options

- Standard, chisel and 90° jaw options
- 30°, 45°, 60° and 75° jaw opening available
- Flexible mounting options
- Part present sensing
- One-step tip adjustment tool






Features, Markets and Applications

COMPACT SIZE	 12% smaller footprint ^(*) Zero protrusion fixed jaw No protrusion of top jaw mechanism below body 	AUTOMOTIVE	STAMPING	
LIGHTWEIGHT	 60% lighter, weighing only 0.27kg (vs 0.56kg) ^(*) Body constructed of lightweight aluminum 		ASSEMBLY	
PERFORMANCE	 60% faster actuation time at 33ms (vs 50ms) ^(*) Compact and powerful, with a grip force up to 1000N at 5 bar Integrated clamp-loss protection 	AEROSPACE	CNC MACHINING FIXTURE/TEST	

ACCELERATE[®] PRESS ROOM GRIPPER

84N1 Series Sheet Metal Gripper with Adjustable Tips







ACCELERATE® PRESS ROOM GRIPPER

84N Series Mounting and Sensor Options







84N Series Sheet Metal Gripper used with Accelerate Lightweight Tooling.



The Accelerate[®] Press Room Sheet Metal Gripper is designed to compliment the Accelerate[®] Collection, providing a complete lightweight and flexible tooling system.

The Accelerate[®] Collection handle parts of any size and shape thoughout the stamping process.

The Accelerate[®] Press Room Sheet Metal Gripper is:

60% lighter* (0.27kg vs 0.56kg)

12% smaller* foot print

60% faster* actuation (33ms vs 50ms)

100% DESTACO innovation

*When compared with our closest Competition



84N1 Standard Fixed Lower Single Jaw, Point Tip Rear Ball Mount

84N1 Chisel Lower Jaw Double Jaw, Peen Tip 32mm Side Ball Mount



84N2 90 deg Jaw Single Tip Serrated Insert Rear Flange Mount Double Blank Detector Sensor



84N2 Standard Fixed Lower Jaw Double Tip Serrated Insert Parallel Swivel Mount Infrared PNP Sensor

Specification	Unit		
Grip Force at 5 bar	Ν	Up to 1000	
Weight (FC00 version)	Kg	.27	
Size L x W x H (closed)	mm	110 x 43 x 43	
Size L x W x H (open)	mm	110 x 43 x 64	
Actuation Time	ms	33	
Life	cycles	5 million	
Minimum Operating Pressure	bar	1	
Opening Angles		30°, 45°, 60°, 75°	
Piston Ø	mm	25	
Air Consumption/Cycle	L	.015	

Dimensions and technical information are subject to change without notice.

GERMANY +49-6171-705-0 europe@destaco.com

FRANCE Tel: +33-4-7354-5001 france@destaco.com UNITED KINGDOM +44-1902-797980 uk@destaco.com

SPAIN +34-936361680 spain@destaco.com NETHERLANDS +31-297285332 benelux@destaco.com

CHINA +86-21-6081-2888 china@destaco.com THAILAND +66-2-326-0812 asia@destaco.com

+91-80-41123421-426

india@destaco.com

INDIA

USA + 1-888-DESTACO + 1-248-836-6700 northamerica@destaco.com

KAT_SG_84N-F_0618_GB